

ARDEX B 36

Chemwatch Material Safety Data Sheet

Issue Date: 21-Jul-2008

NC317ECP

CHEMWATCH 4656-71

Version No:4

CD 2008/2 Page 1 of 10

Section 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME

ARDEX B 36

SYNONYMS

"patching mortar", "Ardex DPM146B"

PRODUCT USE

Cementitious mortar for repair of masonry substrates.

SUPPLIER

Company: Ardex Australia Pty Ltd

Address:

20 Powers Road

Seven Hills


NSW, 2147

AUS

Telephone: 1800 224 070

Fax: +61 2 9838 7817

CHEMWATCH HAZARD RATINGS



Section 2 - HAZARDS IDENTIFICATION

STATEMENT OF HAZARDOUS NATURE

HAZARDOUS SUBSTANCE. NON-DANGEROUS GOODS. According to the Criteria of NOHSC, and the ADG Code.

POISONS SCHEDULE

None

RISK

Causes burns.

Risk of serious damage to eyes.

SAFETY

Keep locked up.

Do not breathe dust.

Avoid contact with eyes.

Wear suitable protective clothing.

Use only in well ventilated areas.

Keep container in a well ventilated place.

To clean the floor and all objects contaminated by this material use water and detergent.

Take off immediately all contaminated clothing.

In case of accident or if you feel unwell IMMEDIATELY

contact Doctor or Poisons Information Centre (show label if

continued...

ARDEX B 36

Chemwatch Material Safety Data Sheet

Issue Date: 21-Jul-2008

NC317ECP

CHEMWATCH 4656-71

Version No:4

CD 2008/2 Page 2 of 10

Section 2 - HAZARDS IDENTIFICATION

possible).

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

| NAME | CAS RN | % |
|------------------------|-------------|--------|
| graded sand | 14808-60-7. | 30-60 |
| portland cement | 65997-15-1 | 10-<30 |
| silica welding fumes | 69012-64-2 | <10 |
| additives, unregulated | | <10 |

Section 4 - FIRST AID MEASURES

SWALLOWED

- For advice, contact a Poisons Information Centre or a doctor at once.
- Urgent hospital treatment is likely to be needed.
- If swallowed do NOT induce vomiting.
- If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.
- Observe the patient carefully.
- Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious.
- Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink.
- Transport to hospital or doctor without delay.

EYE

- If this product comes in contact with the eyes:
- Immediately hold eyelids apart and flush the eye continuously with running water.
 - Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.
 - Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes.
 - Transport to hospital or doctor without delay.
 - Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.

SKIN

- If skin or hair contact occurs:
- Immediately flush body and clothes with large amounts of water, using safety shower if available.
 - Quickly remove all contaminated clothing, including footwear.
 - Wash skin and hair with running water. Continue flushing with water until advised to stop by the Poisons Information Centre.
 - Transport to hospital, or doctor.

INHALED

- If fumes or combustion products are inhaled remove from contaminated area.
- Lay patient down. Keep warm and rested.
- Prosthesis such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.
- Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.
- Transport to hospital, or doctor.

continued...

ARDEX B 36

Chemwatch Material Safety Data Sheet

Issue Date: 21-Jul-2008

NC317ECP

CHEMWATCH 4656-71

Version No:4

CD 2008/2 Page 3 of 10

Section 4 - FIRST AID MEASURES

NOTES TO PHYSICIAN

Treat symptomatically.

For acute or short-term repeated exposures to highly alkaline materials:

- Respiratory stress is uncommon but present occasionally because of soft tissue edema.
 - Unless endotracheal intubation can be accomplished under direct vision, cricothyroidotomy or tracheotomy may be necessary.
 - Oxygen is given as indicated.
 - The presence of shock suggests perforation and mandates an intravenous line and fluid administration.
 - Damage due to alkaline corrosives occurs by liquefaction necrosis whereby the saponification of fats and solubilisation of proteins allow deep penetration into the tissue.
- Alkalis continue to cause damage after exposure.

INGESTION:

- Milk and water are the preferred diluents
- No more than 2 glasses of water should be given to an adult.
- Neutralising agents should never be given since exothermic heat reaction may compound injury.
 - * Catharsis and emesis are absolutely contra-indicated.
 - * Activated charcoal does not absorb alkali.
 - * Gastric lavage should not be used.

Supportive care involves the following:

- Withhold oral feedings initially.
- If endoscopy confirms transmucosal injury start steroids only within the first 48 hours.
- Carefully evaluate the amount of tissue necrosis before assessing the need for surgical intervention.
- Patients should be instructed to seek medical attention whenever they develop difficulty in swallowing (dysphagia).

SKIN AND EYE:

- Injury should be irrigated for 20-30 minutes.
- Eye injuries require saline. [Ellenhorn & Barceloux: Medical Toxicology].

Section 5 - FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA

- There is no restriction on the type of extinguisher which may be used.
- Use extinguishing media suitable for surrounding area.

FIRE FIGHTING

- Alert Fire Brigade and tell them location and nature of hazard.
- Wear breathing apparatus plus protective gloves for fire only.
- Prevent, by any means available, spillage from entering drains or water courses.
- Use fire fighting procedures suitable for surrounding area.
- DO NOT approach containers suspected to be hot.
- Cool fire exposed containers with water spray from a protected location.
- If safe to do so, remove containers from path of fire.
- Equipment should be thoroughly decontaminated after use.

FIRE/EXPLOSION HAZARD

- Non combustible.
- Not considered a significant fire risk, however containers may burn.

May emit poisonous fumes.

May emit corrosive fumes.

continued...

ARDEX B 36

Chemwatch Material Safety Data Sheet

Issue Date: 21-Jul-2008

NC317ECP

CHEMWATCH 4656-71

Version No:4

CD 2008/2 Page 4 of 10

Section 5 - FIRE FIGHTING MEASURES

FIRE INCOMPATIBILITY

None known.

HAZCHEM: None

Personal Protective Equipment

Gas tight chemical resistant suit.

Section 6 - ACCIDENTAL RELEASE MEASURES

EMERGENCY PROCEDURES

MINOR SPILLS

- Remove all ignition sources.
- Clean up all spills immediately.
- Avoid contact with skin and eyes.
- Control personal contact by using protective equipment.
- Use dry clean up procedures and avoid generating dust.
- Place in a suitable labelled container for waste disposal.

MAJOR SPILLS

Moderate hazard.

- CAUTION: Advise personnel in area.
- Alert Emergency Services and tell them location and nature of hazard.
- Control personal contact by wearing protective clothing.
- Prevent, by any means available, spillage from entering drains or water courses.
- Recover product wherever possible.
- IF DRY: Use dry clean up procedures and avoid generating dust. Collect residues and place in sealed plastic bags or other containers for disposal. IF WET: Vacuum/shovel up and place in labelled containers for disposal.
- ALWAYS: Wash area down with large amounts of water and prevent runoff into drains.
- If contamination of drains or waterways occurs, advise Emergency Services.

Personal Protective Equipment advice is contained in Section 8 of the MSDS.

Section 7 - HANDLING AND STORAGE

PROCEDURE FOR HANDLING

- Avoid all personal contact, including inhalation.
- Wear protective clothing when risk of exposure occurs.
- Use in a well-ventilated area.
- Prevent concentration in hollows and sumps.
- DO NOT enter confined spaces until atmosphere has been checked.
- DO NOT allow material to contact humans, exposed food or food utensils.
- Avoid contact with incompatible materials.
- When handling, DO NOT eat, drink or smoke.
- Keep containers securely sealed when not in use.
- Avoid physical damage to containers.
- Always wash hands with soap and water after handling.
- Work clothes should be laundered separately. Launder contaminated clothing before re-use.
- Use good occupational work practice.
- Observe manufacturer's storing and handling recommendations.
- Atmosphere should be regularly checked against established exposure standards to ensure

continued...

ARDEX B 36

Chemwatch Material Safety Data Sheet

Issue Date: 21-Jul-2008

NC317ECP

CHEMWATCH 4656-71

Version No:4

CD 2008/2 Page 5 of 10

Section 7 - HANDLING AND STORAGE

safe working conditions are maintained.

SUITABLE CONTAINER

- Polyethylene or polypropylene container.
- Check all containers are clearly labelled and free from leaks.

STORAGE INCOMPATIBILITY

None known.

STORAGE REQUIREMENTS

- Store in original containers.
- Keep containers securely sealed.
- Store in a cool, dry area protected from environmental extremes.
- Store away from incompatible materials and foodstuff containers.
- Protect containers against physical damage and check regularly for leaks.
- Observe manufacturer's storing and handling recommendations
- Consider storage in bunded areas - ensure storage areas are isolated from sources of community water (including stormwater, ground water, lakes and streams).
- Ensure that accidental discharge to air or water is the subject of a contingency disaster management plan; this may require consultation with local authorities.

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE CONTROLS

| Source | Material | TWA mg/m ³ |
|------------------------------|---------------------------------------|-----------------------|
| Australia Exposure Standards | portland cement (Portland cement (a)) | 10 |

The following materials had no OELs on our records

- graded sand: CAS:14808- 60- 7
- silica welding fumes: CAS:69012- 64- 2

EMERGENCY EXPOSURE LIMITS

| Material | Revised IDLH Value (mg/m ³) | Revised IDLH Value (ppm) |
|-----------------|---|--------------------------|
| graded sand | 50 | |
| portland cement | 5, 000 | |

MATERIAL DATA

Not available. Refer to individual constituents.

INGREDIENT DATA

GRADED SAND:

NOTE: This product contains negligible amount of respirable dust.

PORTLAND CEMENT:

Sensory irritants are chemicals that produce temporary and undesirable side-effects on the eyes, nose or throat. Historically occupational exposure standards for these irritants have been based on observation of workers' responses to various airborne concentrations. Present day expectations require that nearly every individual should be protected against even minor sensory irritation and exposure standards are established using uncertainty factors or safety factors of 5 to 10 or more. On occasion animal no-observable-effect-levels (NOEL) are used to determine these limits where human results are unavailable. An additional approach, typically used by the TLV committee (USA) in determining respiratory standards for this group of chemicals, has been to assign ceiling values (TLV C) to rapidly acting irritants and to assign short-term exposure limits (TLV

continued...

ARDEX B 36

Chemwatch Material Safety Data Sheet

Issue Date: 21-Jul-2008

NC317ECP

CHEMWATCH 4656-71

Version No:4

CD 2008/2 Page 6 of 10

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

STELs) when the weight of evidence from irritation, bioaccumulation and other endpoints combine to warrant such a limit. In contrast the MAK Commission (Germany) uses a five-category system based on intensive odour, local irritation, and elimination half-life. However this system is being replaced to be consistent with the European Union (EU) Scientific Committee for Occupational Exposure Limits (SCOEL); this is more closely allied to that of the USA.

OSHA (USA) concluded that exposure to sensory irritants can:

- cause inflammation
- cause increased susceptibility to other irritants and infectious agents
- lead to permanent injury or dysfunction
- permit greater absorption of hazardous substances and
- acclimate the worker to the irritant warning properties of these substances thus

increasing the risk of overexposure.

Portland cement is considered to be a nuisance dust that does not cause fibrosis and has little potential to induce adverse effects on the lung.

SILICA WELDING FUMES:

Not available

PERSONAL PROTECTION

EYE

- Chemical goggles.
- Full face shield may be required for supplementary but never for primary protection of eyes
- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lens or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59].

HANDS/FEET

- Wear chemical protective gloves, eg. PVC.
- Wear safety footwear or safety gumboots, eg. Rubber.

NOTE:

- The material may produce skin sensitisation in predisposed individuals. Care must be taken, when removing gloves and other protective equipment, to avoid all possible skin contact.
- Contaminated leather items, such as shoes, belts and watch-bands should be removed and destroyed.

OTHER

- Overalls.
- P.V.C. apron.
- Barrier cream.
- Skin cleansing cream.
- Eye wash unit.

RESPIRATOR

| Protection Factor | Half- Face Respirator | Full- Face Respirator | Powered Air Respirator |
|-------------------|-----------------------|-----------------------|------------------------|
| 10 x ES | P1 Air- line* | - - | PAPR- P1 - |
| 50 x ES | Air- line** | P2 | PAPR- P2 |
| 100 x ES | - | P3 | - |

continued...

ARDEX B 36

Chemwatch Material Safety Data Sheet

Issue Date: 21-Jul-2008

NC317ECP

CHEMWATCH 4656-71

Version No:4

CD 2008/2 Page 7 of 10

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

| | | | |
|-----------|---|-------------|----------|
| 100+ x ES | - | Air- line* | - |
| | | Air- line** | PAPR- P3 |

* - Negative pressure demand ** - Continuous flow.

The local concentration of material, quantity and conditions of use determine the type of personal protective equipment required.

For further information consult site specific CHEMWATCH data (if available), or your Occupational Health and Safety Advisor.

ENGINEERING CONTROLS

Local exhaust ventilation usually required. If risk of overexposure exists, wear approved respirator. Correct fit is essential to obtain adequate protection. Supplied-air type respirator may be required in special circumstances. Correct fit is essential to ensure adequate protection.

An approved self contained breathing apparatus (SCBA) may be required in some situations. Provide adequate ventilation in warehouse or closed storage area.

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE

Grey powder; forms slurry in water.

Bulk Density: 1.3 approx.

PHYSICAL PROPERTIES

Alkaline.

Molecular Weight: Not Applicable

Melting Range (°C): Not Available

Solubility in water (g/L): Partly Miscible

pH (1% solution): Not Applicable

Volatile Component (%vol): Not Applicable

Relative Vapour Density (air=1): Not

Applicable

Lower Explosive Limit (%): Not Applicable

Autoignition Temp (°C): Not Applicable

State: Divided Solid

Boiling Range (°C): Not Applicable

Specific Gravity (water= 1): 2.0 approx.

pH (as supplied): Not Applicable

Vapour Pressure (kPa): Not Applicable

Evaporation Rate: Not Applicable

Flash Point (°C): Not Applicable

Upper Explosive Limit (%): Not Applicable

Decomposition Temp (°C): Not Applicable

Viscosity: Not Applicable

Section 10 - CHEMICAL STABILITY AND REACTIVITY INFORMATION

CONDITIONS CONTRIBUTING TO INSTABILITY

- Presence of incompatible materials.
- Product is considered stable.
- Hazardous polymerisation will not occur.

Section 11 - TOXICOLOGICAL INFORMATION

POTENTIAL HEALTH EFFECTS

ACUTE HEALTH EFFECTS

continued...

ARDEX B 36

Chemwatch Material Safety Data Sheet

Issue Date: 21-Jul-2008

NC317ECP

CHEMWATCH 4656-71

Version No:4

CD 2008/2 Page 8 of 10

Section 11 - TOXICOLOGICAL INFORMATION

SWALLOWED

The material can produce chemical burns within the oral cavity and gastrointestinal tract following ingestion.

EYE

The material can produce chemical burns to the eye following direct contact. Vapours or mists may be extremely irritating.

SKIN

The material can produce chemical burns following direct contact with the skin.

Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.

INHALED

Inhalation of dusts, generated by the material during the course of normal handling, may be damaging to the health of the individual.

Effects on lungs are significantly enhanced in the presence of respirable particles.

CHRONIC HEALTH EFFECTS

Long term exposure to high dust concentrations may cause changes in lung function i.e. pneumoconiosis; caused by particles less than 0.5 micron penetrating and remaining in the lung. Prime symptom is breathlessness; lung shadows show on X-ray.

Substance accumulation, in the human body, may occur and may cause some concern following repeated or long-term occupational exposure.

Repeated or prolonged exposure to corrosives may result in the erosion of teeth, inflammatory and ulcerative changes in the mouth and necrosis (rarely) of the jaw.

Bronchial irritation, with cough, and frequent attacks of bronchial pneumonia may ensue.

Gastrointestinal disturbances may also occur. Chronic exposures may result in dermatitis and/or conjunctivitis.

There has been some concern that this material can cause cancer or mutations but there is not enough data to make an assessment.

There is some evidence that inhaling this product is more likely to cause a sensitisation reaction in some persons compared to the general population.

There is limited evidence that, skin contact with this product is more likely to cause a sensitisation reaction in some persons compared to the general population.

TOXICITY AND IRRITATION

Not available. Refer to individual constituents.

GRADED SAND:

unless otherwise specified data extracted from RTECS - Register of Toxic Effects of Chemical Substances.

No data of toxicological significance identified in literature search.

PORTLAND CEMENT:

unless otherwise specified data extracted from RTECS - Register of Toxic Effects of Chemical Substances.

Asthma-like symptoms may continue for months or even years after exposure to the material ceases. This may be due to a non-allergenic condition known as reactive airways dysfunction syndrome (RADS) which can occur following exposure to high levels of highly irritating compound. Key criteria for the diagnosis of RADS include the absence of preceding respiratory disease, in a non-atopic individual, with abrupt onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. A reversible airflow pattern, on spirometry, with the presence of moderate to severe bronchial hyperreactivity on methacholine challenge testing and the lack of minimal lymphocytic inflammation, without eosinophilia, have also been included in the

continued...

ARDEX B 36

Chemwatch Material Safety Data Sheet

Issue Date: 21-Jul-2008

NC317ECP

CHEMWATCH 4656-71

Version No:4

CD 2008/2 Page 9 of 10

Section 11 - TOXICOLOGICAL INFORMATION

criteria for diagnosis of RADS. RADS (or asthma) following an irritating inhalation is an infrequent disorder with rates related to the concentration of and duration of exposure to the irritating substance. Industrial bronchitis, on the other hand, is a disorder that occurs as result of exposure due to high concentrations of irritating substance (often particulate in nature) and is completely reversible after exposure ceases. The disorder is characterised by dyspnea, cough and mucus production.

SILICA WELDING FUMES:

unless otherwise specified data extracted from RTECS - Register of Toxic Effects of Chemical Substances.

TOXICITY

Oral (rat) LD50: 3160 mg/kg

Reports indicate high/prolonged exposures to amorphous silicas induced lung fibrosis in experimental animals; in some experiments these effects were reversible. [PATTYS]

The substance is classified by IARC as Group 3:

NOT classifiable as to its carcinogenicity to humans.

Evidence of carcinogenicity may be inadequate or limited in animal testing.

IRRITATION

No data [RTECS]

MATERIAL

CARCINOGEN

REPROTOXIN

SENSITISER

SKIN

graded sand

IARC:1

CARCINOGEN

IARC: International Agency for Research on Cancer (IARC) Carcinogens: graded sand
Category: WARNING: This substance has been classified by the IARC as Group 1:
CARCINOGENIC TO HUMANS.

Section 12 - ECOLOGICAL INFORMATION

DO NOT discharge into sewer or waterways.
Refer to data for ingredients, which follows:

PORTLAND CEMENT:

DO NOT discharge into sewer or waterways.

SILICA WELDING FUMES:

No data

Section 13 - DISPOSAL CONSIDERATIONS

- Recycle wherever possible.
- Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility can be identified.
- Dispose of by: Burial in a licenced land-fill or Incineration in a licenced apparatus (after admixture with suitable combustible material)
- Decontaminate empty containers. Observe all label safeguards until containers are cleaned and destroyed.

Section 14 - TRANSPORTATION INFORMATION

HAZCHEM: None

NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS:UN, IATA,

continued...

ARDEX B 36

Chemwatch Material Safety Data Sheet

Issue Date: 21-Jul-2008

NC317ECP

CHEMWATCH 4656-71

Version No:4

CD 2008/2 Page 10 of 10

Section 14 - TRANSPORTATION INFORMATION

IMDG

Section 15 - REGULATORY INFORMATION

POISONS SCHEDULE: None

REGULATIONS

Ardex B 36 (CAS: None):
No regulations applicable

graded sand (CAS: 14808-60-7) is found on the following regulatory lists;

- Australia - New South Wales Hazardous Substances Prohibited for Specific Uses
- Australia - New South Wales Hazardous Substances Requiring Health Surveillance
- Australia - South Australia Hazardous Substances Requiring Health Surveillance
- Australia - Tasmania Hazardous Substances Prohibited for Specified Uses
- Australia - Tasmania Hazardous Substances Requiring Health Surveillance
- Australia - Western Australia Hazardous Substances Requiring Health Surveillance
- Australia Exposure Standards
- Australia Hazardous Substances
- Australia Hazardous Substances Requiring Health Surveillance
- Australia High Volume Industrial Chemical List (HVICL)
- Australia Occupational Health and Safety (Commonwealth Employment) (National Standards) Regulations 1994 - Hazardous Substances Requiring Health Surveillance
- Australia Standard for the Uniform Scheduling of Drugs and Poisons (SUSDP) - Schedule 6
- International Agency for Research on Cancer (IARC) Carcinogens
- OECD Representative List of High Production Volume (HPV) Chemicals

portland cement (CAS: 65997-15-1) is found on the following regulatory lists;

- Australia Exposure Standards
- Australia High Volume Industrial Chemical List (HVICL)
- OECD Representative List of High Production Volume (HPV) Chemicals

silica welding fumes (CAS: 69012-64-2) is found on the following regulatory lists;

- GESAMP/EHS Composite List of Hazard Profiles - Hazard evaluation of substances transported by ships
- IMO Provisional Categorization of Liquid Substances - List 1: Pure or technically pure products
- OECD Representative List of High Production Volume (HPV) Chemicals

Section 16 - OTHER INFORMATION

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

A list of reference resources used to assist the committee may be found at:
www.chemwatch.net/references.

The (M)SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

This document is copyright. Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH. TEL (+61 3) 9572 4700.

Issue Date: 21-Jul-2008

Print Date: 21-Jul-2008