



GROUT SHIELD

WATER BASED GROUT SEALER (Does Not Change The Grouts Appearance)

PACKAGING



MIXING



APPLICATION



USES



SUBSTRATES

CEMENT BASED
FLOOR AND WALL
GROUTS

DESCRIPTION

A water based silicone sealer that repels water and shields the grout from contaminants and staining. Does not change the appearance of the grout.

USES

A grout sealer for sanded and fine grouts on exterior and interior floors and walls.

FEATURES

- Does not change appearance
- Shields the grout from contaminants
- Allows the grout to breathe

COVERAGE

3-8m² per coat /250mL
Depending on grout width and porosity

SURFACE PREPARATION

The grout to be sealed must be clean, dry, porous and not contaminated by previous sealers. New grout must have cured for 48 hours before applying the sealer.

TEST AREA

Apply GROUT SHIELD to a small area to test suitability and application before commencing the whole area. Read the label thoroughly before proceeding.

APPLICATION

Apply a coat of GROUT SHIELD, holding the sealer close (2-5cm away) and spray the grout. After 4-5 minutes remove sealer that has not penetrated into the grout with a clean rag or paper towel.

Do not let unpenetrated sealer dry on the surface. To check the performance of the sealer, after 2 hours by applying some water drops to the surface. If water is absorbed apply a second coat. Repeat the procedure until the grout is sealed. Do not wet for 12 hours, but is fully cured in 24 hours.

LIMITATIONS

1. GROUT SHIELD penetrates into the grout and the application should last 5+ years. However, in high wear situations on areas subject to harsh cleaning, chemical wear, more frequent repeat sealing may be required.
2. Do not allow the sealer residue to dry on the surface, as residue will be visible. If this does occur, remove residue with an abrasive bathroom cleaner or baking soda mixed with water.

CAUTION

Use rubber gloves and eye protection when applying product. Flush thoroughly with water product that is in contact with skin or eyes or if ingested seek medical assistance. MSDS are available upon request.

CONSTRUCTION
CHEMICALS

● **ADELAIDE** 135 CORMACK RD (Cnr Davis St) WINGFIELD 5013 PH: (08) 8243 7888 FAX: (08) 8243 7800
 ● **BRISBANE** 45 COULSON ST WACOL 4076 PH: (07) 3271 2944 FAX: (07) 3271 3892
 ● **MELBOURNE** 11 GABRIELLE CT BAYSWATER NORTH 3153 PH: (03) 9761 4711 FAX: (03) 9761 4748
 ● **PERTH** 11 COLLIE ST WELSHPOOL 6106 PH: (08) 9356 9999 FAX: (08) 9356 9955
 ● **SYDNEY** 31-33 NEWTON RD WETHERILL PARK 2164 PH: (02) 9756 3533 FAX: (02) 9756 3534
 ● **AUCKLAND** 16 CARPENTER RD EAST TAMAKI PH: (09) 273 5444 FAX: 0800 266 236
 ● **KUALA LUMPUR** LOT 2 JALAN KECAPI 33/2 ELITE INDUSTRIAL ESTATE OFF JALAN BUKIT KEMUNING
 40000 SHAB ALAM PH: (603) 5122 2522 FAX: (603) 5122 2526

www.constructionchemicals.com.au

"The information contained in this technical publication is based on our current knowledge and experience and is provided as a guide only. In view of the many factors that may affect application it is the users sole responsibility to ensure suitability for a specific purpose."