

NATURAL SEALER

(CLEAR – DOES NOT CHANGE APPEARANCE OF SUBSTRATE)

PRODUCT DATA SHEET

DESCRIPTION A clear solvent based sealer that penetrates deep into the concrete and masonry surfaces and hydrolyses in the pores and capillaries forming a weather and chemical barrier without changing the appearance.

USES Apply to concrete, bricks, stone and masonry surfaces to preserve its original appearance.

FEATURES

- ✘ Quick acting - will repel water in approximately 2 hours
- ✘ Long lasting tests have shown years of dependable protection
- ✘ Seals surface from moisture and protects surface from atmospheric chemical attack
- ✘ Will not darken or yellow with age
- ✘ Reduced weather staining - vertical surfaces tend to be self-cleaning
- ✘ May be recoated any time

COVERAGE (Approximate) 8-10m²/litre/coat

SURFACE PREPARATION Surfaces to be coated must be absorbent, sound, clean and free of oil, grease, efflorescence and other contaminants. Completely remove previous coatings and do not apply to non-absorbent surfaces. The new surface can be wet but ponding water must be removed. New concrete should be cured for 28 days.

To check suitability of a sealer apply a test area before commencing.

APPLICATION Apply by brush, long nap roller or low pressure spray (35-100kpa)

Apply evenly with steady even strokes - do not flood surface. Work Natural Sealer into surface irregularities and apply liberally. Apply two coats for normal application, however three coats may be required for very porous surfaces. Apply the second coat immediately. ie. wet on wet. When recoating after areas have been in use for some time scrub area with detergent and a stiff broom to remove dirt and grease and hose down with clean water and let dry before recoating. On very porous surfaces application should be repeated until the surface is saturated
Solvent: XYLENE or equivalent.

STORAGE Keep in a cool dry place away from open fires, heater and stoves etc.

SAFETY INSTRUCTIONS Contains flammable solvents in the liquid state. Do not smoke during application or apply in the presence of naked flames, electrical equipment or sparks. Ensure adequate ventilation during application and drying period. Avoid contact with skin or eyes, breathing vapour or mist spray. Keep out of children's reach.

FIRST AID *If swallowed do not induce vomiting. Give a glass of water and contact a doctor or Poison Information Centre.*