

Waterproofing Warehouse  
4/12 Strathaird Road  
Bundall, Gold Coast, 4217  
www.wpw.com.au

### **ADEKA ULTRA SEAL MC- PRODUCT CONCRETE COVERAGE REQUIREMENTS**

Concrete Strength	180 (kgf/cm <sup>2</sup> ) 2556 (psi)	210 (kgf/cm <sup>2</sup> ) 2982 (psi)	240 (kgf/cm <sup>2</sup> ) 3408 (psi)	270 (kgf/cm <sup>2</sup> ) 3834 (psi)	300 (kgf/cm <sup>2</sup> ) 4260 (psi)
Minimum Concrete Coverage	<b>10 cm</b> <b>4 (inch)</b>	<b>9.3 (cm)</b> <b>3.7 (inch)</b>	<b>8.9 (cm)</b> <b>3.5 (inch)</b>	<b>8.6 (cm)</b> <b>3.4 (inch)</b>	<b>8.1 (cm)</b> <b>3.2 (inch)</b>

1 (kgf/cm<sup>2</sup>) = 14.2 (psi)    1 (cm) = 0.3937 (inch)

If concrete coverage is less than 3.2 inches, check KBA-1510FP data sheet

email - [admin@wpw.com.au](mailto:admin@wpw.com.au) for additional information